

CHAINSAW and BAR OIL

High Performance Chain and Bar Oil designed for lubrication of chain, bar and sprocket on all types of chainsaws and chain driven machinery. Formulated and manufactured with advanced tackifier technology that resists throw off during high speed applications.

Applications

Formulated for lubrication of the chain, bar and sprocket on all types of chainsaws, using either hand operated or automatic oilers.

It is also recommended for other chain driven machinery, including motor cycles, lawnmowers, lumber carriers and farm equipment.

Benefits

- Wear protection and cleanliness of components
- Extends bar, chain and sprocket life
- Advanced tackifier technology to increase oil adhesion and tackiness
- Protection of internal working components
- Improved oil fluidity in colder weather due to HYDRO-SYN™ base oils
- Reduced chain stretch over operating life

TEST DESCRIPTION	ASTM	TEST RESULT
Description	Visual	Clear/Amber
ISO Viscosity Grade		160
Viscosity, cSt @ 40°C, mm ² /s	D-445	28.5
Viscosity, cSt @ 100°C, mm ² /s	D-445	6.7
Viscosity Index	D-2270	205
Density @ 15°C, kg/L	D-4052	0.861
Pour Point, °C	D-5950	-42
Flash Point (COC), °C	D-92	216
PRODUCT CODE		88880

Typical formulation specifications at time of production, minor variations may occur. 88880v20 DG/GS 2/20